

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

## CHAINBAR OILS (ISO 100 - 220)

## PRODUCT DESCRIPTION

Chainbar Oils are made from a blend of high quality base stocks and selected additives to ensure optimum performance and long life lubrication of chains and their sprockets.

Chainbar Oils contain tackifiers to resist "throw-off" ensuring that a continuous wear, reducing adhesive, lubricating film is kept on the chain mechanisms and maintaining maximum benefit of the anti-wear and anti-corrosion additives systems.

The fluidity of Chainbar Oils ensures that they are ideally suited for manual application or for units fitted with automatic oilers. Chainbar Oils exhibit excellent penetration of chain links.

Hi-Tec suggests that the equipment manufacturers' recommendations for grade, performance requirements and general operating conditions should be checked prior to use.

## **TYPICAL PROPERTIES**

| Property              | ASTM Method | Results |       |       |
|-----------------------|-------------|---------|-------|-------|
| Item code (HI8-)      |             | 2816    | 2819  | 2820  |
| ISO Grade             | -           | 100     | 150   | 220   |
| Appearance            | Visual      | Amber   | Amber | Amber |
| Density Kg/Lt @ 15°C  | D1298       | 0.894   | 0.897 | 0.901 |
| Viscosity cSt @ 100°C | D445        | 11.8    | 15.5  | 20    |
| @ 40°C                | D445        | 100     | 150   | 220   |
| Viscosity Index       | D2270       | 107     | 106   | 105   |
| Flash Point COC,°C    | D92         | >200    | >200  | >200  |

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 4 Litres and 1 Litre.

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: February 2020

KH022062/1





