

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

ENGINE FLUSH

PRODUCT DESCRIPTION

Engine Flush is an advanced chemical formulation suitable for use in all internal combustion engines. It is a special formulation designed to dissolve and remove the built-up sludge, dirt, varnish and other contaminants within the engine's lubrication system, thus providing a cleaner environment for the new oil. It also helps to free sticky valves and hydraulic lifters.

Engines over time and through normal operation develop sludge, drawing in dirt and other contaminants. All these undesirable materials decrease the engine's efficiency and performance and may in time lead to engine failure.

Sludge and debris are hard to remove as they settle and attach in the corners and crevices of the oil pan, engine passageways, and the oil pump. Changing the oil as specified by the engine manufacturer helps to minimise these deposits but does not eradicate them. The only way to keep the engine as clean as possible is by the regular use of an engine flush.

Engine Flush contains a special blend of detergents and additives that will detach and remove sludge, carbonaceous deposits, rust and fouling material, leaving the engine internally clean. It also contains lubricating additives that ensure maximum lubrication of engine parts during flushing.

Engine Flush is compatible with all engine oils and is suitable for all cars and light van petrol and diesel engines including turbocharged models.

300mL of **Engine Flush** treats up to 5 litres of engine oil.

DIRECTIONS FOR USE

Prior to oil change, add **Engine Flush** to the old engine oil. Run the vehicle for 15 minutes to operating temperature. Turn the engine off and drain all the oil thoroughly. Change the oil filter and recharge the engine with the recommended quantity and grade of new oil.

HEALTH AND SAFETY

Keep Out Of Reach Of Children. Avoid contact with eyes and skin. Wash skin and other body parts thoroughly with water. If in eyes, flush with plenty of water for at least 15 minutes and consult a doctor. If swallowed, seek medical advice immediately or contact the **Poisons Information Centre on 13 11 26**. Provide adequate ventilation when using in confined spaces. Store away from sources of heat and direct sunlight, preferably in temperatures ranges of 15°C to 30°C. When stored as specified, the product has a shelf life of two (2) years minimum. Spills and leaks can be absorbed with material such as sand, earth or saw dust. Dispose of waste products thoughtfully or through Chemical Waste Disposal Authority. The Safety Data Sheet is available upon request.









Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

ODUCT DATA SHEET

PHYSICAL PROPERTIES

Brown liquid with petroleum odour, does not mix with water. **Appearance**

Transparency Density at 20°C 0.81 ± 0.01

Available in: Bulk, 20 Litres and 300 mL

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI8-3302 (bulk)

> HI8-3302-0020 HI14-EF-300

Effective: March 2020

MR023030/1



