



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

FLEETMASTER CK-4 EXTREME 15W/40

PRODUCT DESCRIPTION

Fleetmaster CK-4 Extreme 15W/40 is an API CK-4 heavy duty diesel engine oil formulated using the latest synthetic technology base oils for use in severe duty high speed four stroke diesel engines with DPF, cooled EGR and other exhaust treatment systems, both turbo-charged and normally aspirated. It is designed to offer greater durability and protection due to its increased shear stability and reduced oxidative thickening, abrasive wear, bore polishing and piston deposits. **Fleetmaster CK-4 Extreme 15W/40** can be used in 2017 model vehicles as well as those requiring Euro VI emission standards, and can replace CJ-4 engine oils. It is backwards compatible with most applications where engine manufacturers currently recommend CJ-4, CI-4 Plus, CI-4 and CH-4 performance specifications.

BENEFITS

- Increased shear stability
- Reduced oxidative thickening for increased viscosity stability
- Lower piston deposits
- Protection against particulate filter blocking and soot-related viscosity increase
- Increased wear protection due to less abrasive wear and bore polishing
- Better fuel economy
- Increased resistance to aeration
- Protection against catalyst poisoning
- Higher levels of protection and performance compared to API CJ-4

APPLICATIONS

- 2017 model vehicles as well as those requiring Euro VI emission standards
- Backward compatible with engines requiring CJ-4, CI-4 Plus, CI-4 and CH-4

SPECIFICATIONS:

Fleetmaster CK-4 Extreme 15W/40 meets or exceeds the following demanding performance requirements:

API: CK-4, CJ-4, CI-4 Plus, CI-4, CH-4

API: SN, SM, SL

ACEA: E9, E7

Euro Emission Standards: I, II, III, IV, V, VI

OEMs: Allison TES 439
CAT ECF-3
Cummins CES 20086 (Approved)
Ford WSS-M2C171-F1, WSS-M2C171-E
Detroit Diesel DDC 93K222
Deutz DQC III-18LA, DQC III-10LA
JASO DH-2
Mack EO Premium Plus, EOS-4.5 (Approved)
MAN M3775, M3575
MB 228.31
MTU 2.1
Renault VI RLD-3 (Approved)
Volvo VDS-4.5 (Approved)

Always consult your vehicle owner's manual for the manufacturer's recommendations.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL PROPERTIES

Property	ASTM Method	Typical Results
Density (kg/m ³)	D-1298	0.878
Viscosity (cSt) @ 100°C	D-445	15.0
@ 40°C	D-445	115.3
CCS (cP) @ -20°C	D-5293	6230
Viscosity Index	D-2270	133
HTHS (cP)	D-4683	4.0
Noack (% wt)	D-5800	11
Flash Point COC (°C)	D-92	218
Pour Point (°C)	D-97	-39
TBN (mg KOH/g)	D-2896	10.0
Sulphated Ash (% wt)	D-874	1.0
Phosphorus (% wt)	D-5185	0.11
Magnesium (% wt)	D-5185	0.10
Zinc (% wt)	D-5185	0.13
Calcium (% wt)	D-5185	0.10

Available in: Bulk, 1000 Litres, 200 Litres and 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI2-2206

Effective: March 2022

MR223013/1



AUSTRALIAN FAMILY OWNED SINCE 1989

