



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

### SUPER 60

#### PRODUCT DESCRIPTION

**Super 60** (SAE 25W/60) is a specialised engine oil for all naturally aspirated and turbocharged four stroke gasoline passenger car and motorcycle engines. It meets and exceeds the API Service Classifications SG/CD. It gives vastly improved protection against engine wear, high temperature oxidation deposits and sludge formation as well as protection against low temperature "black sludge" development.

#### CHARACTERISTICS

**LONGER ENGINE LIFE.** **Super 60** provides increased engine life since the minimal wear rates associated with quality SF engine oil are decreased by at least 30%. Newly developed anti-wear additives minimise wear under all service conditions to rings, cylinders, bearings, timing gear, valve train and all moving engine surfaces.

**BLACK SLUDGE BEATEN.** The increased levels of powerful dispersants and detergents of **Super 60** maintain clean engines under all service conditions. The special active ashless dispersants inhibit formation of black sludge, especially under the constant cold temperature operation of urban motoring which is a major cause of this harmful sludge. Engine passages are kept clean to ensure full-bodied lubricant reaches every critical engine component requiring lubrication.

**HIGH TEMPERATURE PERFORMANCE.** The careful selection of thermally stable base oils, oxidation inhibitors and detergents enhances performance. High temperature deposits and lacquers associated with oxidation and nitration (occurs in lean burn fuelled engines) are avoided so that peak engine performance is always available under the extremes of sustained high speed highway motoring. Viscosity thickening is a parameter of oxidation. **Super 60** contributes to less oxidation and more protection from piston deposits compared to conventional SF engine oils (when tested in the ASTM Sequence IIIE engine).

**RUST & CORROSION.** Protection by high levels of alkali reserve additives neutralises those acidic corrosive combustion products which have been scavenged past the rings. Rust inhibitors overcome the rust inducing condensation tendencies in cooling engines after engine shut-down.

#### SPECIFICATIONS

**Super 60** meets or exceeds the following demanding performance requirements:

API: SG/CD

FORD: M2C 153E (D & C), GM 6085M, 6048M,

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

### TYPICAL PROPERTIES

| Property                        | ASTM Method | Results |
|---------------------------------|-------------|---------|
| Density (kg/Lt) @ 15°C          | D-1298      | 0.898   |
| Viscosity (cSt) @ 100°C         | D-445       | 26      |
| @ 40°C                          | D-445       | 298     |
| Viscosity Index                 | D-2270      | 115     |
| Pour Point (°C)                 | D-97        | -24     |
| Flash Point COC (°C)            | D-92        | 223     |
| TBN (mg KOH/g)                  | D-2896      | 5.3     |
| Sulphated Ash (% wt)            | D-874       | 0.86    |
| Phosphorus (% wt)               | D-1091      | 0.07    |
| Zinc (% wt)                     | A/A         | 0.08    |
| Magnesium (% wt)                | A/A         | 0.10    |
| Nitrogen (% wt)                 | A/A         | 0.05    |
| Foaming Characteristics         | -           | -       |
| All Sequences (10min settling)  | D-892       | Pass    |
| Rust Prevention Characteristics | D-665       | Pass    |

**Available in:** Bulk, 200 Litres, 20 Litres, 10 Litres and 5 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au). Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)"

**Item code:** HI1-2030

**Effective:** February 2020

MR022011/1



AUSTRALIAN FAMILY OWNED SINCE 1989

