



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

SAFETY DATA SHEET

Page 1 of 9

Issue Date: 13 January 2017

DD50 Coolant Green

Version: 5

Product name: DD50 Coolant Green

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)
ADDRESS: PO Box 322 Castle Hill NSW 1765
5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: DD50 Coolant Green

OTHER NAMES: DD50 Green

MANUFACTURER'S PRODUCT CODE: HI8-3090

USE: Glycol based engine coolant/antifreeze premix

ADDITIONAL INFORMATION: Refer to Product Information Sheet for additional information.

OTHER INFORMATION: Visit our website: www.hi-tecoils.com.au
Email: hitecoils@hi-tecoils.com.au

2. HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: HAZARDOUS SUBSTANCE
NON-DANGEROUS GOODS
Hazard classification according to criteria of NOHSC and GHS.
Dangerous goods classification according to Australian Dangerous Goods Code.

CLASSIFICATION: Acute Toxicity – Oral Category 4

POISON SCHEDULE: S5

GHS LABEL ELEMENTS:



SIGNAL WORD: WARNING



AUSTRALIAN FAMILY OWNED SINCE 1989





SAFETY DATA SHEET

2. HAZARDS IDENTIFICATION (CONT)

HAZARD STATEMENT:	H302 Harmful if swallowed
GENERAL:	P101 If medical advice is needed, have product container or label at hand P102 Keep out of reach of children P103 Read label before use
PREVENTATIVE:	P264 Wash thoroughly after handling P270 Do not eat, drink or smoke when using this product
RESPONSE:	P301 + P312 IF SWALLOWED: Call the POISON INFORMATION CENTRE on 13 11 26 or doctor/physician if you feel unwell P330 Rinse mouth
DISPOSAL:	P501 Dispose of contents/container in accordance with local regulations
OTHER INFORMATION:	Used coolants may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used oils should be handled with caution and skin contact avoided as far as possible.

3. IDENTIFICATION / COMPOSITION OF INGREDIENTS

CHEMICAL CHARACTERISTICS:	Liquid	
INGREDIENTS:-		
CHEMICAL ENTITY:	CAS No.	PROPORTION
Ethylene Glycol	107-21-1	45-55%
Other non hazardous ingredients		To 100%
OTHER INFORMATION:		

4. FIRST AID MEASURES

HEALTH EFFECTS

SWALLOWED:	If a quantity is ingested SEEK IMMEDIATE MEDICAL ATTENTION. Give water or milk to drink. DO NOT induce vomiting. If vomiting occurs get immediate medical attention due to aspiration into lungs risk. Symptoms may include nausea, vomiting, abdominal cramps, diarrhoea, lumbar pain shortly after ingestion, and possibly narcosis and death. Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow
EYE:	Immediately irrigate with copious amounts of water for at least 15 minutes. Eyelids to be held open. In all cases of eye contamination it is a sensible precaution to seek medical advice. If irritation occurs, seek medical advice.



SAFETY DATA SHEET

4. FIRST AID MEASURES (CONT)

SKIN:	Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. If irritation occurs, seek medical advice. High pressure injection through the skin requires URGENT medical attention for possible incision, irrigation and/or debridement. Contact with hot material may require treatment by a physician for burns (Do not remove material).
INHALED:	Remove victim from exposure to fresh air – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through face mask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage and seek urgent medical aid.
FIRST AID FACILITIES:	Normal washroom facilities are generally suitable. Ensure an eye wash station and safety shower is available and ready for use.
ADVICE TO DOCTOR:	Treat symptomatically.
OTHER INFORMATION:	Keep water and mild soap near work site.

5. FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

HAZARDS OF USE/STORAGE:	Product will not burn unless preheated.
HAZARDS FROM COMBUSTION PRODUCTS:	There is no risk of an explosion from this product under normal circumstances if it is involved in a fire. Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. Fire decomposition products: carbon dioxide, carbon monoxide, acrid smoke, irritating fumes.
FIRE-FIGHTING RECOMMENDATIONS:	Not Combustible. Use extinguishing media suited to burning materials. Do not use water jet.
SUITABLE EXTINGUISHING MEDIA:	Use water, foam, carbon dioxide or dry chemical.
PROTECTIVE MEASURES:	We suggest that protective clothing be made from the following materials: rubber, PVC.
REACTIVITY:	This product will not undergo polymerisation reactions.



SAFETY DATA SHEET

Page 4 of 9

Issue Date: 13 January 2017

DD50 Coolant Green

Version: 5

6. ACCIDENTAL RELEASE MEASURES

SPILLS & DISPOSAL:

Slippery when spilt. Avoid accidents, clean up immediately.

CLEAN-UP PROCEDURE - SMALL SPILLS (20L or less): Minor spills do not normally need any special cleanup measures

CLEAN-UP PROCEDURES - LARGE SPILLS (Greater than 20L): In the event of a major spill, prevent spillage from entering drains or water courses.

PERSONAL PRECAUTIONS: As a minimum, wear overalls, goggles and gloves. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

OTHER INFORMATION:

PROCEDURES IN CASES OF LEAKAGE OR BREAKAGE: Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Can be slippery on floors, especially when wet. Recycle containers wherever possible after careful cleaning.

After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

SAFE STORAGE CONDITIONS:

Keep containers closed at all times. Store in a cool place out of direct sunlight. Check containers regularly for leaks.

CORROSIVENESS:

Not corrosive.

STORAGE REGULATIONS:

Store in a well ventilated place away from ignition sources, oxidising agents, foodstuffs and clothing. Avoid contact with eyes, skin and clothing. Do not ingest.
Keep containers closed when not in use.





SAFETY DATA SHEET

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL EXPOSURE STANDARDS: Vapour TWA 52mg/m³, STEL 104 mg/m³; particulate TWA 10mg/m³.

OTHER EXPOSURE INFORMATION: Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).

ENGINEERING CONTROLS: Maintain concentration below recommended exposure limit. Special ventilation is not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standard or the Manufacturer's recommended exposure standard.

RESPIRATORY PROTECTION: A respirator is not normally required. Airborne concentrations should be kept at lowest level possible. If vapours, mists or dusts are generated and the recommended exposure limit for the product is exceeded, use appropriate AS/NZS 1715/1716 approved half-face filter respirator suitable for organic vapours or air supplied respirator are worn. Air supplied respirators should always be worn when the airborne concentration of the contaminant or the oxygen content of the air is unknown

EYE PROTECTION: Safety glasses, goggles or face shield as appropriate.

HAND PROTECTION: Use solvent resistant glove: nitrile, PVC or neoprene.

FOOTWEAR: Enclosed footwear.

BODY PROTECTION: Overalls or similar protective apparel.

HYGIENE MEASURES: Always wash hands before eating, drinking, smoking or using the toilet. If contamination occurs, change clothing. Launder contaminated clothing before reuse. Discard internally contaminated gloves.

SPECIAL PROTECTIVE MEASURES: Isolate from sources of heat, naked flames or sparks.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid

APPEARANCE: Yellow green liquid.

COLOUR: Yellow green

ODOUR: Slight

FREEZING/MELTING POINT: -37°C





SAFETY DATA SHEET

Page 6 of 9

Issue Date: 13 January 2017

DD50 Coolant Green

Version: 5

9. PHYSICAL AND CHEMICAL PROPERTIES (CONT)

BOILING POINT:	116°C at radiator cap pressure, 108 °C at atmospheric pressure.
DENSITY @ 15°C (kg/L):	1.07 – 1.08
FLASHPOINT (ASTM D-93), Closed Cup:	116
EVAPORATION RATE (Butyl acetate =1):	0.01
SOLUBILITY IN WATER:	Soluble.
SOLUBILITY IN ORGANIC SOLVENTS:	Soluble in methanol and diethyl ether
VISCOSITY @ 40 °C (mm ² /s):	No data
pH:	7.6 – 8.5
OTHER INFORMATION:	These physical data and other properties do not constitute a specification.

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under normal conditions of use.
CONDITIONS TO AVOID:	No additional remark.
INCOMPATIBLE MATERIALS:	Strong oxidising agents, acids, alkalis
HAZARDOUS REACTIONS:	Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire: carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. This will only occur after heating to dryness. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.
HAZARDOUS POLYMERISATION:	Will not occur.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY:	Low toxicity in animals - LD50 Oral (rat) < 4700mg/kg LD50 Dermal (rabbit) < 9530mg/kg Note that there is a marked difference in acute oral toxicity between animals and humans, humans being more susceptible than animals. The estimated fatal dose for humans is 100ml
SKIN CORROSION/IRRITATION:	May cause skin irritation; prolonged contact may cause dermatitis.
SERIOUS EYE:DAMAGE/IRRITATION:	May cause eye irritation





SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION (CONT)

RESPIRATORY OR SKIN SENSITISATION:	Not expected to be a sensitiser
GERM CELL MUTAGENICITY:	No evidence of mutagenic activity
CARCINOGENICITY:	Not carcinogenic in animal studies
REPRODUCTIVE TOXICITY:	Not expected to impair fertility
SPECIFIC TARGET ORGAN TOXICITY (STOT) - SINGLE EXPOSURE:	May cause drowsiness or dizziness. Inhalation of vapours or mists may cause irritation to the lungs and respiratory system
SPECIFIC TARGET ORGANTOXICITY (STOT) - REPEATED EXPOSURE:	May cause damage to organs or organ systems through prolonged or repeated exposure. Toxic to liver and kidneys
ASPIRATION HAZARD:	Not considered an aspiration hazard

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	
ACUTE TOXICITY:	Fish – Low toxicity: LC/EC/IC50 > 100mg/l Aquatic invertebrate – Low toxicity: LC/EC/IC50 > 100mg/l Algae – Low toxicity: LC/EC/IC50 > 100mg/l Microorganisms – Low toxicity: LC/EC/IC50 > 100mg/l
CHRONIC TOXICITY:	Fish – NOEC/NOEL > 100mg/l Aquatic invertebrate – NOEC/NOEL > 100mg/l Algae – No data available Microorganisms – No data available
PERSISTENCE AND DEGRADABILITY:	Biodegradable.
BIOACCUMULATIVE POTENTIAL:	Does not bioaccumulate significantly.
MOBILITY IN SOIL:	Dissolves in water. If product enters soil, one or more constituents will be mobile and may contaminate groundwater.
OTHER ADVERSE EFFECTS:	No data available.



SAFETY DATA SHEET

Page 8 of 9

Issue Date: 13 January 2017

DD50 Coolant Green

Version: 5

13. DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATION:

Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. This product should be suitable for landfill. However, check with local Waste Disposal Authority before sending there. Note that product properties may have been changed in use; significantly altering its suitability for landfill. Please do NOT dispose into sewers or waterways. .

14. TRANSPORT INFORMATION

ROAD & RAIL TRANSPORT:

ADG REQUIREMENT

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

MARITIME TRANSPORT:

IMO/IMDG REQUIREMENT

Not classified as a Dangerous Good according to the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT:

ICAO/IATA REQUIREMENT

Not classified as a Dangerous Good according to the criteria of the International Maritime Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

POISON SCHEDULE:

S5

PACKING & LABELLING:

No special packaging or labelling requirements.

AUSTRALIAN INVENTORY STATUS:

All components are listed or exempted.

16. OTHER INFORMATION

CONTACT PERSON/POINT:

General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

SAFETY DATA SHEET

Page 9 of 9

Issue Date: 13 January 2017

DD50 Coolant Green

Version: 5

16. OTHER INFORMATION (CONT)

- LITERATURE REFERENCES:
- * NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
 - * NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
 - * NOHSC: 10005 List of Designated Hazardous Substances.
 - * NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
 - * NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
 - * NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
 - * NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
 - * NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
 - * NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.
 - * SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
 - * ADG: Australian Dangerous Goods Code
 - * MSDS of component materials.

LAST CHANGE:

Supersedes document issued 17th April 2015

Reason/s for revision: Minor editorial changes to meet GHS requirements.

MR711031/1

END OF SDS



AUSTRALIAN FAMILY OWNED SINCE 1989

