



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

AUTO TRANS STOP LEAK

PRODUCT DESCRIPTION

Auto Trans Stop Leak is a heavy duty lubricant sealer designed to help stop transmission fluid leaks. It aids in sealing hard-to-reach leaks without the need for disassembling or removing parts. This fluid contains a special blend of additives that enable penetration into cracked, hardened and shrunken rubber seals causing them to swell and form a seal against leaks.

Auto Trans Stop Leak is an ideal solution to help stop leaks from seals on drive shafts, transmission pans, input shafts and valve bodies. It also enhances the oxidation stability of oil leading to smoother operation of the transmission.

It is recommended that the transmission oil be treated every 3 months to prevent sudden cracks from occurring unexpectedly and ensure ongoing performance.

Under normal circumstances, 300 mL of **Auto Trans Stop Leak** is sufficient to treat a standard transmission. Some transmissions, particularly older types, may require several treatments before efficiency and benefits are noticed or restored.

A transmission leak implies a crack or shrinkage in a seal in the transmission which in turn can cause the vehicle to malfunction. But such leaks can also be caused by clogged oil filters so it is important to check the filter before attempting to repair transmission seals. If leaks persist after treatment, it may be that the seal or the gasket is severely damaged that it should be replaced.

DIRECTIONS FOR USE

Add contents of the bottle to transmission oil in the ratio of 1 part **Auto Trans Stop Leak** to 10 parts oil.

HEALTH AND SAFETY

Keep out of reach of children. For first aid and emergency refer to Material Safety Data Sheet or contact the **Poisons Information Centre on 131126.**

Keep in a cool dry place away from direct sunlight. Do not store above 50°C. Do not use near fire or naked flame. Do not incinerate product containers even when empty. Dispose of waste residues and empty cans thoughtfully or through authorized chemical waste disposal authorities.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Available in: 300 mL

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI14-ATSL-300

Effective: March 2020

MR023030/1



AUSTRALIAN FAMILY OWNED SINCE 1989

